

## AUPO temperature fuse P-5A-F series



Dimension (P-5A-F series) ( mm )

a	b	c	d	e
11.5±0.5	38±3	∅0.6±0.02	∅3.3±0.2	3.6 or below

### ▶ P-5A-F

Model NO	Rated functioning temp.(Tf)	Fusing-off temperature	Holding temperature (Th)	Maximum temp .limit (Tm)	Rated current (Ir)	Rated voltage (Ur)	Safety Approval						RoHS
							UL	CUL	VDE	PSE	CCC	KTL	
P0-5A-F	84°C	82±2°C	55°C	180°C	5A	250V	☑	☑	☑	☑	☑		☑
P1-5A-F	102°C	98±2°C	63°C	180°C	5A	250V	☑	☑	☑	☑	☑		☑
P2-5A-F	115°C	112±3°C	75°C	180°C	5A	250V	☑	☑	☑	☑	☑		☑
P3-5A-F	125°C	120±3°C	85°C	180°C	5A	250V	☑	☑	☑	☑	☑		☑
P4-5A-F	130°C	126±2°C	90°C	180°C	5A	250V	☑	☑	☑	☑	☑		☑
P5-5A-F	135°C	131±3°C	90°C	180°C	5A	250V	☑	☑	☑	☑	☑		☑
P9-5A-F	138°C	135±2°C	93°C	180°C	5A	250V	☑	☑	☑	☑	☑		☑
P7-5A-F	150°C	145±3°C	105°C	180°C	5A	250V	☑	☑	☑	☑	☑		☑