

AUPO temperature fuse P-F series



Dimension (P-F series) (mm)

a	b	c	d	e
9.0±0.5	38±3	∅0.54±0.05	∅2.5±0.1	3.0 or below

▶ P-F

Model NO	Rated functioning temp.(Tf)	Fusing-off temperature	Holding temperature (Th)	Maximum temp .limit (Tm)	Rated current (Ir)	Rated voltage (Ur)	Safety Approval						RoHS
							UL	CUL	VDE	PSE	CCC	KTL	
P1-F	102°C	98±2°C	76°C	180°C	2A	250V	☑	☑	☑	☑	☑	☑	☑
P2-F	115°C	112±3°C	85°C	180°C	2A	250V	☑	☑	☑	☑	☑	☑	☑
P3-F	125°C	120±3°C	97°C	180°C	2A	250V	☑	☑	☑	☑	☑	☑	☑
P4-F	130°C	126±2°C	102°C	180°C	2A	250V	☑	☑	☑	☑	☑	☑	☑
P5-F	135°C	131±3°C	105°C	180°C	2A	250V	☑	☑	☑	☑	☑	☑	☑
P9-F	138°C	135±2°C	108°C	180°C	2A	250V	☑	☑	☑	☑	☑	☑	☑
P7-F	150°C	145±3°C	120°C	180°C	2A	250V	☑	☑	☑	☑	☑	☑	☑